



## Staff Loudspeaker Unit

STS-SU1-G / STS-SU1-B /  
STS-SU1-SS

Our free-standing combined speaker and directional microphone module for the staff side has an integral loudspeaker, microphone with a semi-rigid stem, adjustable neck and mute switch.

### Physical Data

Dimensions	Height – 370mm (6.30") Width – 95mm (2.76") Depth – 150mm (3.94")
Weight	820g (1.80lbs)
Construction	Stainless Steel
	Mild Steel
Finish	Grey Powder Coated Leatherette
	Black Textured Powder Coated
	Brushed Stainless Steel

### Technical Data

Speaker	RMS	5W
	Impedance	4Ω
	Output	SPL 1W @ 1M 85dB
	Frequency Response	150Hz - 10300Hz
Microphone	Directional Response	Cardioid
	Frequency Response	150Hz - 10500Hz
	Sensitivity	49.5dB+ 2dB @ 1kHz (0dB=1V/pa)
	Impedance	1.6K Ohms+ 3-% @ 1kHz

### Applications

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports

### Standards

- CE, ROHS and WEEE compliant



Talk to us now:  
+44 (0) 1732 223900 (UK & ROW)  
+1 616 392 3400 (US & Canada)  
[www.contacta.co.uk](http://www.contacta.co.uk)