

# Staff Loudspeaker Unit with Dual Mute Switch

Our free-standing combined speaker and directional microphone module for the staff side has an integral loudspeaker, microphone with a semi-rigid stem, adjustable neck and dual mute switch.

The dual mute switch gives the following options when used with a window intercom system:

- Sound working on both staff and customer sides of the counter
- Mute the staff side
- Mute both staff and customer sides

### **Physical Data**

Dimensions	Height – 370mm (6.30") Width – 95mm (2.76") Depth – 150mm (3.94")	
Weight	820g (1.80lbs)	
Construction	Stainless Steel	
	Mild Steel	
Finish	Grey Powder Coated Leatherette	
	Black Textured Powder Coated	

#### **Technical Data**

Speaker	RMS	5W
	KIVIS	300
	Impedance	$4\Omega$
	Output	SPL 1W @ 1M 85dB
	Frequency Response	150Hz - 10300Hz
Microphone	Directional Response	Cardioid
	Frequency Response	150Hz - 10500Hz
	Sensitivity	49.5dB+ 2dB @ 1kHz (0dB=1V/pa)
	Impedance	1.6K Ohms+ 3-% @ 1kHz



STS-SU1-3W-B / STS-SU1-3W-G

## **Applications**

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports

#### **Standards**

ROHS and WEEE compliant

Talk to us now: +44 (0) 1732 223900 (UK & ROW) +1 616 392 3400 (US & Canada) www.contacta.co.uk

